

R2000 COOLING SYSTEM



Specifications

- Factory set at 50 psi adjustable to 100 psi
 - 6 gallon reservoir (15 gallon available)
 - 115 VAC 50 / 60 Hz 1 ph
 - 230 VAC 50 / 60 Hz 1 ph
 - 13.4 / 6.7 amp:60 Hz 1 ph
 - 230 / 190 VAC 50 / 60 Hz 3 ph
 - 460 / 380 VAC 50/60 Hz 3 ph
 - 2.6 / 1.3 amp:60 Hz3 ph
 - 30,000 BTU
 - Dimensions: 23"L x 16"W x 19.5"H
- 1/4" FPT (water in / out) with 5/8" LH Standard Inert Gas Fitting
 - 8 foot power cord. 1 ph only
- Visible water level / water flow sight glass
 - Thermal overload
 - Net weight: 68 lbs/31 kg
 - Foam packed for UPS shipment

R2000: Rotary GEAR Pump (only)

- 3.5 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit Product No. P2001)

System Features

- Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
 - All units are plumbed with copper tubing and reinforced hose.
 - New extended life pump
 - No external plumbing is required because of closed loop water system.
- A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
- Water filter on pump inlet protects pump and extends pump life.

Equipment	UP TO
M.I.G. guns	1000 amps
T.I.G. torches	1000 amps
PLASMA Welders / Cutters	300 amps
RESISTANCE Welders	150 KVA
INDUCTION Welding	10 KW

SKU: N/A | Categories: [Machines](#), [Water Recirculators](#) |



GALLERY IMAGES



