

## R2200 V COOLING SYSTEM



### Specifications

- Factory set at 50 psi adjustable to 100 psi
- 15 gallon reservoir (6 gallon available)
  - 115 or 230 VAC / 1 ph-50 / 60 Hz
  - 8.2 / 4.1 amp:60 Hz
  - 30,000 BTU
- Dimensions: 23"L x 16"W x 25.5"H
- 1/2" FPT fittings-water in and out
  - 8 foot power cord
- Visible water level and water flow sight glass
  - Net weight: 70 lbs / 32 kg

### R2200 V: Rotary VANE Pump

4.0 gpm at 50 psi

### System Features

- Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions.
  - All units are plumbed with copper tubing and reinforced hose.
    - New extended life pump.
  - Air flows into patented high efficiency radiator first for maximum efficiency.
    - No external plumbing is required because of closed loop water system.
- A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
- Water filter on pump inlet protects pump and extends pump life.

Equipment	UP TO
M.I.G. guns	1000 amps
T.I.G. torches	1000 amps
PLASMA Welders / Cutters	300 amps
RESISTANCE Welders	150 KVA
INDUCTION Welding	10 KW

**SKU:** N/A | **Categories:** [Machines](#), [Water Recirculators](#) |



## GALLERY IMAGES



